

beroNet Telephony Appliance



Compatible with:



Engineered and
Made in Germany

- Cloud Managed: Remotely Manage & Monitor your Appliance
- There is a module for every Scenario - PRI, BRI, Analog & GSM
- Hybrid: Up to 2 Modules on one Device
- Install any Operating System on the Appliance
- No moving Parts, Long-Life and Reliable
- Operational use of under 24W Saving €200 per year in electricity
- 100% Aluminium construction, Robust and Lightweight
- Completely Silent & can be placed anywhere in any Office
- PCM Connector extends your Appliance with an additional beroNet Gateway



Technical Details

Features:

- Intel Atom N2800 2x1,86Ghz
- 2GB RAM (optional 4GB)
- 30 GB SSD (optional 120GB)
- 4 x external USB 2.0, gigabit ethernet port
- keyboard and monitor support
- TDM bridging over 2 beroNet devices through PCM bus interconnection, 8.192 kB/s
- built-in beroNet VoIP Card (BF400/BF1600)
- 2 module slots (analog, ISDN, GSM)
- fanless, silent and robust
- shipped with bootstick incl. several sample PBX's
- compliance: CE (EN55022, EN55024, EN60950)

Devices:

Media Function	BNTA16	BNTA64
G.711 incl. HW EC	16 channels	64 channels
G.726 incl. HW EC	4 channels	16 channels
G.729 incl. HW EC	4 channels	16 channels
G.723 incl. HW EC	4 channels	16 channels
T.38	4 channels	16 channels

Available Modules:

- ISDN: 1 PRI, 2 PRI, 4 BRI
- Analog: 4 FXO, 4 FXS, 8 FXS
- GSM: 2 GSM
- Hybrid: 2 BRI/2 FXS

Dimensions and Weight:

- dimensions: 340 x 255 x 46 mm
- mounting IU industry with optional 19" brackets or wallmountable chassis
- weight: 2 kg (depending on module configuration)
- power supply: 110-230V operating 12V DC at 3A

Environment:

- storage temperature: -20° to 70°C
- operating temperature: 0° to 40°C
- humidity: up to 90 %, non-condensing

Friedrichstraße 231 - 10969 Berlin
Tel. : +49 30 2593890 - E-Mail: sales@beronet.com

